



TECHNICAL DATA SHEET

PEC-MAT® Turf Reinforcement Mat

6' x 75' Rolls, 50 sq yd

PEC-MAT® is the permanent soft armor solution for many hard armor applications. PEC-MAT protects seed and soil during germination and provides long term turf reinforcement for established vegetation.

Its dense web design guards seed and soil from wind, rain and storm-water forces, while retaining moisture and solar energy to promote seedling development. The new vegetation's roots entwine with PEC-MAT to produce a reinforced turf capable of withstanding flow velocities up to 20 feet per second and a shear stress of 6 pounds per square foot.

PRODUCT TEST DATA		
Physical Property	Test Method	Typical Value
Material		thermally welded PVC monofilaments
Color		Green
Weight	ASTM D-3776	28 oz sq yd
Thickness	Measured	0.1 in
Porosity	CWD 02215-86	72%
Tensile Strength (length/width)	ASTM D-4595-86	12 x 7 lbs/in
Elongation (length/width)	ASTM D-4595-86	75% x 75%
Secant Tensile-Modulus (length/width)	ASTM D-4595-86	30 x 15 lbs/in
Breaking Toughness (length/width)	ASTM D-4595-86	6 x 3.5 lbs sq in
Conformity (length/width)	ASTM D-1388-75	50 x 33 in./lb x 10 ⁻⁴
QUV Stability @ 2000 hrs	ASTM G-53-84	85% prop. ret.
Low Temp Brittleness	ASTM D-746	-35F
pH Range		2-12 pH
Manning Roughness Coefficient N		.02
Max. Flow Velocity		20 ft/sec
Max. Recommended Shear Stress		6 lbs sq ft
Max. Stake Load		25 lbs

Test results represent Minimum Average Roll Values (MARV) with the exception of weight which is a typical result.

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.