

## TECHNICAL DATA SHEET

### IVI CONTAINMENT POOLS

Stock sizes: 3' x 6' 3' x 9' 4' x 8' 8' x 8'  
 Custom sizes and dimensions are available upon request

The IVI Containment Pool is designed to fit under cars, trucks, light plants, generator sets, pumps, and heavy equipment. These rugged pools will catch and contain all oil, hydraulic fluid, gas, antifreeze, water, and grease that may leak or drip from engines and equipment.

Manufactured using durable 22 ounce yellow PVC with RF leak-proof welded seams, IVI Containment Pools feature 3" side walls that contain closed cell, HDPE solid foam rods that insure durable use. They are lightweight, reusable, and easily deployed. Eliminate problems from equipment leaks and drips in your yard or jobsite with IVI Containment Pools



The IVI 22 oz. Containment Pool fabric meets or exceeds the following specifications:

Properties	Test Method	Typical Value
<b>Material Weight</b>	FS 5040 / ASTM D-3776	22 oz sq yd
<b>Yarn</b>		Polyester
<b>Count</b>		16 x 16
<b>Denier</b>		1500
<b>Grab Tensile</b>	FS 5100 / ASTM D-5034	400 x 400 lbs/in
<b>Tongue Tear</b>	FS 5134 / ASTM D-2261	132 x 143 lbs
<b>Adhesion</b>	FS 5970 / ASTM D-751	28 lbs/ 2"
<b>Hydrostatic Resistance</b>	ASTM D-751	881 lbs sq in
<b>Mullen Burst</b>	ASTM D-3786	924 lbs sq in
<b>Abrasion</b>	FS 5306 / ASTM D-3884	Start -250, Complete 400 cycles
<b>Cold Crack</b>	FS 5874 / ASTM D-2136	-40F
<b>High Temperature</b>		176F Continuous, 200F Intermittent
<b>Treatments</b>		Anti-Mildew & UV Pigments
<b>Finish</b>		Matte

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.