



TECHNICAL DATA SHEET

IVI Oil Containment Boom

Standard Features

18 oz. yellow high visibility PVC coated polyester

5/16" vinyl coated galvanized steel top load cable for deployment

6" Closed-cell polyethylene flotation

Aluminum universal end connectors

5/16" Ballast chain

12" Solid PVC skirt

Section Length: 100' bundled in 200' deployment lots

Also available in 22 oz. PVC coated polyester

Properties	Test Method	Typical Value
Material Weight	FS 5040 / ASTM D-3776	18.5 oz sq yd
Yarn		Polyester
Count		18 x17
Denier		1000 x 1300
Grab Tensile	FS 5100 / ASTM D-5034	375 x 375 lbs/in
Tongue Tear	FS 5134 / ASTM D-2261	100 x 100 lbs
Adhesion	FS 5970 / ASTM D-751	26 lbs/ 2"
Cold Crack	FS 5874	-30F
Treatments		Anti-Mildew & UV Pigments
Finish		Matte

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.

NOTE: Specified fabrics will be supplied per order: Permeable and non permeable. Buoyancy increased when specified. Ballast chain increased when specified.